

Motion detectors



The right detector for any application.

Motion detectors

Motion detector IS 3360

Multi-storey car park, entrances, equipment room

Specifications	Interface	Type of installation		Version		IP rating	EAN
		Surf.-mount.	Con-cealed	Round	Square		
PIR / 360° / max. 20m	COM1	•			•	IP54	4007841 010478
PIR / 360° / max. 20m	COM1	•		•		IP54	4007841 033446
PIR / 360° / max. 20m	COM1		•		•	IP20	4007841 033460
PIR / 360° / max. 20m	COM1		•	•		IP20	4007841 033453
PIR / 360° / max. 20m	PF	•			•	IP54	4007841 010515
PIR / 360° / max. 20m	PF	•		•		IP54	4007841 033477
PIR / 360° / max. 20m	PF		•		•	IP20	4007841 033491
PIR / 360° / max. 20m	PF		•	•		IP20	4007841 033484

Switching capacity, floating (PF): no SELV, max. 10 A, 240VAC / 24VDC, min. 100mA, 12VAC/DC
 Switching capacity, COM1: max. 2000W, max. 8 LEDs



SMART REMOTE READY

3000 series.
 For all interfaces.
 For even greater flexibility.



Motion detector IS 3360 MX Highbay

High-bay warehouse space

Specifications	Interface	Type of installation		Version		IP rating	EAN
		Surf.-mount.	Con-cealed	Round	Square		
PIR / 360° / max. 18m	COM1	•			•	IP54	4007841 033569
PIR / 360° / max. 18m	COM1		•		•	IP20	4007841 033576
PIR / 360° / max. 18m	PF	•			•	IP54	4007841 033583
PIR / 360° / max. 18m	PF		•		•	IP20	4007841 033590

Switching capacity, floating (PF): no SELV, max. 10 A, 240VAC / 24VDC, min. 100mA, 12VAC/DC
 Switching capacity, COM1: max. 2000W, max. 8 LEDs



SMART REMOTE READY

SMART REMOTE READY



Motion detector IS 3180

Corridor, passageway, side room

Specifications	Interface	Type of installation		Version		IP rating	EAN
		Surf.-mount.	Con-cealed	Round	Square		
PIR / 180° / 8-20m or 4-8m	COM1	•			•	IP54	4007841 009113
PIR / 180° / 8-20m or 4-8m	PF	•			•	IP54	4007841 010508

Switching capacity, floating (PF): no SELV, max. 10 A, 240VAC / 24VDC, min. 100mA, 12VAC/DC
 Switching capacity, COM1: max. 2000W, max. 8 LEDs

Motion detector HF 3360

WC, washroom, stairwell, side room

Specifications	Interface	Type of installation		Version		IP rating	EAN
		Surf.-mount.	Con-cealed	Round	Square		
HF / 360° / Ø 1-8m	COM1	•			•	IP54	4007841 011734
HF / 360° / Ø 1-8m	COM1	•		•		IP54	4007841 033668
HF / 360° / Ø 1-8m	COM1		•		•	IP20	4007841 033675
HF / 360° / Ø 1-8m	COM1		•	•		IP20	4007841 033682
HF / 360° / Ø 1-8m	PF	•			•	IP54	4007841 101546
HF / 360° / Ø 1-8m	PF	•		•		IP54	4007841 033699
HF / 360° / Ø 1-8m	PF		•		•	IP20	4007841 033705
HF / 360° / Ø 1-8m	PF		•	•		IP20	4007841 033712

Switching capacity, floating (PF): no SELV, max. 10 A, 240VAC / 24VDC, min. 100mA, 12VAC/DC
 Switching capacity, COM1: max. 2000W, max. 8 LEDs



SMART REMOTE READY

ALWAYS THE RIGHT CHOICE FOR YOUR APPLICATION

Available in 4 designs, the 3000-series sensors are the perfect match for your surroundings. Whether round or square, surface mounted or concealed, you are always sure to find the right sensor from the 3000 series.

MAXIMUM COMPATIBILITY

With up to 5 interfaces, you will always find the right connection to existing systems or systems still to be planned.

CONTROLLED FROM THE FLOOR

The remote controls that are available make it very easy to set the 3000 series from the floor. Or with the Smart Remote