


Plugs and connectors – Plugs


to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.



Plug ProTOP
enclosure with thread lock and safety slide

IP 44
Std. Pack. Qty: 10


A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	3	147A	148A				
16	4		151A	152A	153A		
16	5			13A			
32	3	159	160				
32	4		163	164	165		
32	5			14A			



Plug StarTOP
screwless, with SafeCONTACT, enclosure with thread lock and safety slide

IP 44
Std. Pack. Qty: 10


A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	3	947	948				
16	4		951	952	953	954	
16	5			33			
32	3	711	712				
32	4		717	719	723		
32	5			34			



Plug AM-TOP
single part body

IP 44
Std. Pack. Qty: 10


A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	3	247	248	249		2168	2271
16	4	250	251	252	253	254	255
16	5	256	257	3	2014	2189	2243
32	3	259	260	261		2195	2341
32	4	262	263	264	265	266	267
32	5	268	269	4	2015	2244	2178



Plug PowerTOP Xtra
rubberised grip area, highly heat resistant contact carrier, frame terminals, nickel plated contacts, cable gland and sealing, strain relief and protection against kinking

IP 44
Std. Pack. Qty: 5


A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
63	3	13101	13102				
63	4		13105	13106	13107		
63	5		13111	13112			



Plug PowerTOP
highly heat resistant contact carrier, nickel plated contacts, cable gland and external cable grip

IP 44
Std. Pack. Qty: 10

A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	3	3918	3919	3920			
16	4	3925	3927	3926	3928		
16	5	3934	3936	3935			
32	3	3942	3943	3944			
32	4	3945	3946	3947	3948		
32	5	3951	3952	3977			



Angled plug VarioTOP
cable entry hood rotating up to 60° to the left or the right, 3981 and 3980: in colour code 3983 and 3982: in electric grey

IP 44
Std. Pack. Qty: 10

A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	5		3981	3980			
16	5		3983	3982			