







## Plugs and connectors – Plugs

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request.

 <p><b>Angled plug</b> with grommet, nickel plated, contacts</p> <p>IP 44 Std. Pack. Qty: 10</p>	<b>A</b>	<b>P</b>	<b>110 V</b> 50 a. 60 Hz	<b>230 V</b> 50 a. 60 Hz	<b>400 V</b> 50 a. 60 Hz	<b>500 V</b> 50 a. 60 Hz	<b>&gt;50 - 500 V</b> 100-300 Hz   300-500 Hz	
		16 3	1410	1411				
 <p><b>Angled plug</b> with grommet, nickel plated, contacts</p> <p>IP 44 Std. Pack. Qty: 10</p>	<b>A</b>	<b>P</b>	<b>110 V</b> 50 a. 60 Hz	<b>230 V</b> 50 a. 60 Hz	<b>400 V</b> 50 a. 60 Hz	<b>500 V</b> 50 a. 60 Hz	<b>&gt;50 - 500 V</b> 100-300 Hz   300-500 Hz	
		16 4	1410	891	315			
 <p><b>Angled plug</b> with grommet, nickel plated, contacts</p> <p>IP 44 Std. Pack. Qty: 10</p>	<b>A</b>	<b>P</b>	<b>110 V</b> 50 a. 60 Hz	<b>230 V</b> 50 a. 60 Hz	<b>400 V</b> 50 a. 60 Hz	<b>500 V</b> 50 a. 60 Hz	<b>&gt;50 - 500 V</b> 100-300 Hz   300-500 Hz	
		32 3	3312	3306				
		32 4		3646	3987			
		32 5		3424	3266			
 <p><b>Plug AM-TOP</b> single part body, cable gland and sealing, strain relief and protection against kinking</p> <p>IP 67 Std. Pack. Qty: 10</p>	<b>A</b>	<b>P</b>	<b>110 V</b> 50 a. 60 Hz	<b>230 V</b> 50 a. 60 Hz	<b>400 V</b> 50 a. 60 Hz	<b>500 V</b> 50 a. 60 Hz	<b>&gt;50 - 500 V</b> 100-300 Hz   300-500 Hz	
		16 3	277	278	279			
		16 4	280	281	282	283	284	285
		16 5	286	287	288			
		32 3	289	290	291			
		32 4	292	293	294	295	296	297
		32 5	298	299	300			
 <p><b>Plug PowerTOP</b> with external cable grip, highly heat resistant contact carrier and nickel plated contacts</p> <p>IP 67 Std. Pack. Qty: 10</p>	<b>A</b>	<b>P</b>	<b>110 V</b> 50 a. 60 Hz	<b>230 V</b> 50 a. 60 Hz	<b>400 V</b> 50 a. 60 Hz	<b>500 V</b> 50 a. 60 Hz	<b>&gt;50 - 500 V</b> 100-300 Hz   300-500 Hz	
		16 3	3794	3796	3799			
		16 4	3807	3811	3809	3810		
		16 5	3819	3823	3821			
		32 3	3829	3830	3832			
		32 4	3839	3844	3841	3842		
 <p><b>Plug PowerTOP Xtra</b> rubberised grip area, highly heat resistant contact carrier, frame terminals, nickel plated contacts, cable gland and sealing, strain relief and protection against kinking</p> <p>IP 67 Std. Pack. Qty: 5</p>	<b>A</b>	<b>P</b>	<b>110 V</b> 50 a. 60 Hz	<b>230 V</b> 50 a. 60 Hz	<b>400 V</b> 50 a. 60 Hz	<b>500 V</b> 50 a. 60 Hz	<b>&gt;50 - 500 V</b> 100-300 Hz   300-500 Hz	
		63 3	13201	13202	13203			
		63 4	13204	13205	13206	13207	13208	13209
		63 5	13210	13211	13212	13213		13214
		125 3	13215	13216				
		125 4	13217	13218	13219	13220		
	125 5	13223	13224	13225	13226		13227	