



Wood with nails: Heavy duty AX™ carbide teeth demolition blades



Up to 50x longer life than standard Bi-Metal blades. Carbide teeth deliver long life and extreme durability in the toughest applications. Cuts through hardened screws and fasteners.
 Up to 2x faster than standard Bi-Metal blades. A fast and aggressive 5 Tpi tooth pattern allows for the fastest cutting in nail embedded wood and a wide range of construction materials (wood/nails/bolts/screws/cast iron/asphalt roofing felt shingles).
 Up to 25% more cuts per charge vs. standard Bi-Metal blades. Optimised for use with cordless reciprocating saws.
FANG TIP™: For faster plunge cutting and reaching into restricted areas.
NAIL GUARD™: Protects the tooth during nail impacts for increased durability and lifetime.
 Sloped shape: Excellent for plunge cutting and reaching into restricted areas.
 Thick 1.27 mm robust blade body for precise straight cuts.
 25 mm blade height for improved stability and minimum vibration.
 Best for wood / nails / hardened fasteners demolition

Blade length (mm)	Tooth pitch (mm)	Teeth per inch	Ref. No.	Image 1	Image 2	Image 3	Image 4	Image 5	Image 6	Image 7	Image 8	Pack quantity	Min. order quantity	Article Number	EAN Code
150	5	5	-	10 - 100	10 - 100	Ø 10 - 100	Yes	Yes	Yes	Yes	Yes	1	1	48005221	045242483716
												5	1	48005521	045242521104
230	5	5	-	10 - 175	10 - 175	Ø 10 - 175	Yes	Yes	Yes	Yes	Yes	1	1	48005226	045242483723
												5	1	48005526	045242521111
300	5	5	-	10 - 250	10 - 250	Ø 10 - 250	Yes	Yes	Yes	Yes	Yes	1	1	48005227	045242483730
												5	1	48005527	045242521128

Wood with nails: Heavy duty AX™ demolition blades



FANG TIP™: For faster plunge cutting and reaching into restricted areas.
NAIL GUARD™: Protects the tooth during nail impacts for increased durability and lifetime.
Strong: Thick 1.27mm blade body and 25mm height for maximum robustness and life making it ideal for wood with nails or bolts.
Fast: Aggressive 5 Tpi tooth geometry removes more material per stroke for faster cutting.
Sloped shape: Excellent for plunge cutting and reaching into restricted areas.
Shatter resistant: Bi-Metal construction allows the blade to bend and flex without breaking.

Blade length (mm)	Tooth pitch (mm)	Teeth per inch	Ref. No.	Image 1	Image 2	Image 3	Image 4	Image 5	Image 6	Image 7	Image 8	Pack quantity	Min. order quantity	Article Number	EAN Code
150	5	5	-	10 - 100	10 - 100	10 - 50	Yes	Yes	Yes	Yes	Yes	5	1	48005021	045242082988
												25	1	48008021	045242082285
230	5	5	-	10 - 175	10 - 175	10 - 50	Yes	Yes	Yes	Yes	Yes	5	1	48005026	045242082995
												25	1	48008026	045242082292
300	5	5	-	10 - 250	10 - 250	10 - 50	Yes	Yes	Yes	Yes	Yes	5	1	48005027	045242083022
												25	1	48008027	045242082308

Wood with nails: THIN KERF demolition blades



FANG TIP™: For faster plunge cutting and reaching into restricted areas.
NAIL GUARD™: Protects the tooth during nail impacts for increased durability and lifetime.
Strong: 1.27 mm thick blade body and 19mm height for good strength and blade life making it ideal for wood with nails or bolts.
Fast: Aggressive 5 Tpi geometry removes more material per stroke for faster cutting.
Long sloped shape: Excellent for plunge cutting and reaching into restricted areas.
Shatter resistant: Bi-Metal construction allows the blade to bend and flex without breaking.

Blade length (mm)	Tooth pitch (mm)	Teeth per inch	Ref. No.	Image 1	Image 2	Image 3	Image 4	Image 5	Image 6	Image 7	Image 8	Pack quantity	Min. order quantity	Article Number	EAN Code
150	5	5	S611DF	10 - 100	10 - 100	Ø 10 - 100	Yes	Yes	Yes	Yes	Yes	5	1	48005035	045242082698
												50	1	48016035	045242084791
230	5	5	S1111DF	10 - 175	10 - 175	Ø 10 - 175	Yes	Yes	Yes	Yes	Yes	5	1	48005036	045242082704
												50	1	48016036	045242084661
300	5	5	S1411DF	10 - 250	10 - 250	Ø 10 - 250	Yes	Yes	Yes	Yes	Yes	5	1	48005037	045242082711
												50	1	48016037	045242084807