35



Nothing but **HEAVY DUTY.****

C12 RT

M12™ SUB COMPACT ROTARY **TOOL**

- Versatile cordless solution for cutting and removal applications
 REDLINK" overload protection electronics in tool and battery
 pack deliver best in class system durability
 Variable speed (5000 32,000 rpm)
 0.8 mm 3.2 mm collet fits all current accessories in the market

- O Spindle lock mechanism for easy accessory changes
 Superior ergonomics and lightweight
 Individual battery cell monitoring optimises tool run time and ensures long term pack durability
 Fuel gauge displays remaining charge
 Flexible battery system: works with all Milwaukee® M12"



11		٠.

	V.= V	
Battery pack capacity (Ah)	=	
No. of batteries supplied	0	
Charger supplied	_	
No load speed (rpm)	5000 - 32,000	
Collet capacity (mm)	0.8 / 1.6 / 2.4 / 3.2	
Weight with battery pack (kg)	0.6	
Supplied in	_	
Article Number	4933427183	



M12

C12 MT

M12™ SUB COMPACT **MULTI-TOOL**

- Versatile cordless solution for cutting and removal applications
 REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
 Variable speed (5000 20,000 rpm) and 1.5° left/right oscillation movement allows quick completion of professional applications into materials such as metal, wood and plastic
 Will accept competitor accessories
 Individual battery cell monitoring optimises tool run time and ensures long term pack durability
 Fuel gauge displays remaining charge
 REDLITHIUM-ION™ battery pack delivers up to 2x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies
- technologies Flexible battery system: works with all Milwaukee® M12™ batteries
- Supplied with an adapter, plunge cut blade OSC 112, sanding backing pad, 5 x sanding sheets



	C12 MT-0	C12 MT-402B
Battery pack capacity (Ah)	-	4.0
No. of batteries supplied	0	2
Charger supplied	-	80 min
Oscillation angle left/ right (°)	1.5	1.5
No load speed (rpm)	5000 - 20,000	5000 - 20,000
Weight with battery pack (kg)	_	1.2
Supplied in	-	Tool bag
Artiola Number	4022427100	4022441700



M18 BMT M18™ COMPACT MULTI-TOOL

- o Up to 50% faster and versatile cordless solution for cutting and
- or proson a laster and velsatile cordiness solution for cutaing and removal applications with corded performance

 REDLINK** overload protection and constant speed electronics in tool deliver best in class durability and performance

 12 variable speed settings from 12,000 18,000 orbits per minute and 3.4° oscillation movement allows quick completion of professional applications into materials such as metal, wood and plastic.
- and plastic

 Productivity enhancing FIXTEC tool free blade change with universal blade change adaptor included to accept all
- with universal blade change adaptor included to accept all competitor blades

 REDLITHIUM-ION™ battery pack delivers up to 2x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies

 Unique cutting depth stop adaptor to prevent over-cutting in material
- material

 Unique dust extraction kit to keep the work space dust-free
- when connected to an AC or DC extraction system
 Brightest LED workspace illumination
 Flexible battery system: works with all Milwaukee® M18**



MIS BMI-0	M18 BM1-4210
-	1 x 2.0 & 1 x 4.0
0	2
	80 min
1.7	1.7
12,000 - 18,000	12,000 - 18,000
	1.7
_	Kitbox
4933446203	4933446272
	 0 1.7 12,000 - 18,000

M18

ACCESSORIES

MULTITOOL

Universal blade reception makes Milwaukee® blades compatible with the most popular oscillating tools.

Catal	ogue product description	Teeth per inch	Width (mm)	Length (mm)	Article Number	
a	19 mm plunge cut blade. Plunge / recess / flush cutting in wood and PVC.	16	19	42	48900015	
b	32 mm plunge cut blade. Plunge / recess / flush cutting in wood and PVC.	16	32	42	48900030	
С	32 mm fast cut Japanese tooth blade. For fast , clean cuts in soft and hard wood.	14	32	42	48900055	
d	64 mm Bi-Metal wide blade. For cuts in sheet metal, nail embedded wood, plastic and fibreglass.	18	64	42	48900050	
	80 mm flush cut segmented blade. For accurate and flush cuts in wood and plastics.	18	80	20	48900045	*
f	80 mm Titanium flush segmented blade. Titanium coating for best wear resistance and double the lifetime. For accurate and flush cuts in sheet metal, nail embedded wood, plastic and fibreglass.	18	80	20	48900035	-
g	Grout removal blade. For removing damaged grout between wall or floor tiles. Also good for cutting grooves in drywall.	Carbide grit	64		48900100	
h	Flush cut carbide grit blade. For cutting grooves and slots in plaster, drywall and grout.	Carbide grit	30	20	48900110	
i	Sanding pad		93	93	48902000	
	Sanding paper. Hook & Loop. 8 pc		93	93	48902060	
	pack.		93	93	48902080	0 0
			93	93	48902120	
			93	93	48902240	