

M18 BRAIW | M18™ 3/8" RIGHT ANGLE IMPACT WRENCH

- Compact right angle impact wrench measures 307 mm in length making it ideal for working within confined spaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Full metal gearbox and gears for superior durability and maximum torque
- Compact 53 mm head design
- Multi-handle design for multiple hand positions and maximum comfort
- 3/8" square drive for use with universal sockets
- 2 speed settings for wider range of applications
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M18 BRAIW-0	
No load speed (rpm)	0 - 1500 / 0 - 2250
Tool reception	3/8" square
Impact rate (ipm)	0 - 2400 / 0 - 3400
Max. torque (Nm)	40 / 76
Weight with battery pack (EPTA) (kg)	1.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933447899
EAN Code	4002395006670

M18 ONEFLT | M18 FUEL™ LOCKBOLT TOOL WITH ONE-KEY™

- The M18 FUEL™ lockbolt tool with ONE-KEY™ is an optimised cordless solution that delivers fast, easy installations while maintaining performance, durability, and size
- 20,000 N of pulling force with a stroke length of 30 mm gives you the power to complete the larger applications effortlessly
- Installs up to 1,200 aluminium 6.4 mm lockbolts with one fully charged M18™ 5.0 Ah battery pack
- Increased productivity with faster lockbolt installations
- Installs HUCK® fasteners 4.8 mm and 6.4 mm including Bobtail® Magna-Grip®, C6L®, C120L® and Hucktainer®. All HUCK® nose assemblies and adapters are sold separately. When installing Hucktainers® an additional outer housing is required from MILWAUKEE®. HUCK® is a trade marks of Huck International Inc. and Howmet Aerospace Inc
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 ONEFLT-0X	M18 ONEFLT-502X
Max. pulling force [N]	20,000	20,000
Lockbolt diameter range [mm]	4.8 and 6.4 (Hucktainer® : 9.53 mm)	4.8 mm and 6.4 mm (Hucktainer® : 9.53 mm)
Lockbolt fastener type	Bobtail®,C120L®,C6L®,Hucktainer®,Magna-Grip®	Bobtail®,C120L®,C6L®,Hucktainer®,Magna-Grip®
Stroke length (mm)	30	30
Dimensions (mm)	317 x 63 x 273	317 x 63 x 273
Weight with battery pack (EPTA) (kg)	2.8 (M18 B5)	2.8 (M18 B5)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article number	4933478637	4933478639
EAN code	4058546348304	4058546348328

M18 ONEFPRT | M18 FUEL™ RIVET TOOL WITH ONE-KEY™

- The M18 FUEL™ rivet tool with ONE-KEY™ is an optimised cordless solution that delivers fast, easy riveting while maintaining performance, durability, and size
- Pulls up to 900 rivets with a rivet size of 4.8 mm in aluminium or 500 rivets with a size of 6.4 mm in aluminium on a fully charged M18™ 2.0 Ah battery pack
- Fasten all blind rivets including aluminium, steel, stainless steel and copper from 4.8 mm, 6.0 mm, 6.4 mm and 7.0 mm to give you a bigger range of applications to be completed
- 20,000 N of pulling force with a stroke length of 30 mm gives you the power to complete the larger diameters effortlessly
- The premium steel alloy 3-jaw design delivers more work between jaw changes
- Tool-free access to easily clean jaws. On-board nose piece storage and wrench for user convenience
- The transparent mandrel collector allows you to see when the mandrel collector is full, avoiding any mandrel jammings and minimising down time to unblock jammings also avoiding costly repairs at the same time
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

	M18 ONEFPRT-0X	M18 ONEFPRT-202X
Max. pulling force [N]	20,000	20,000
Max. rivets popped with M18 B2 battery [mm]	900 x 4.8 / 500 x 6.4	900 x 4.8 / 500 x 6.4
Rivet diameter range [mm]	4.8 - 7.0	4.8 - 7.0
Stroke length (mm)	30	30
Dimensions (mm)	317 x 63 x 273	317 x 63 x 273
Weight with battery pack (EPTA) (kg)	2.5 (M18 B2)	2.5 (M18 B2)
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B2 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933478601	4933478603
EAN Code	4058546347949	4058546347963



PERFECT MATCH

RETENTION NOSE PIECES SET FOR M18 FUEL™ RIVET TOOL WITH ONE-KEY™

Article Number 4932478961



C18 PCG/600 | M18™ CAULK GUN WITH 600 ML TUBE

- Up to 4500 N of force. Min 40% higher than previous MILWAUKEE® caulk gun
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	C18 PCG/600A-201B	C18 PCG/600T-201B
Max. pushing force (N)	4500	4500
Speed settings	6	6
Standard equipment	600 ml aluminium	600 ml transparent
Weight with battery pack (EPTA) (kg)	2.3 (M18 B2)	2.3 (M18 B2)
Kit included	1 x M18 B2 Battery pack, M12-18 C Charger, Tool bag	1 x M18 B2 Battery pack, M12-18 C Charger, Tool bag
Article Number	4933448758	4933441810
EAN Code	4002395810802	4002395002399

C18 PCG/400 | M18™ CAULK GUN WITH 400 ML TUBE

- Up to 4500N of force. Min 40% higher than previous MILWAUKEE® caulk gun
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	C18 PCG/400T-201B
Max. pushing force (N)	4500
Speed settings	6
Standard equipment	400 ml transparent tube
Weight with battery pack (EPTA) (kg)	2.3 (M18 B2)
Kit included	1 x M18 B2 Battery pack, M12-18 C Charger, Tool bag
Article Number	4933441814
EAN Code	4002395002382

C18 PCG/310 | M18™ CAULK GUN WITH 310 ML CANISTER

- Up to 4500 N of force. Min 40% higher than previous MILWAUKEE® caulk gun
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



	C18 PCG/310C-201B
Max. pushing force (N)	4500
Speed settings	6
Standard equipment	310 ml canister cartridge holder
Weight with battery pack (EPTA) (kg)	2.3 (M18 B2)
Kit included	1 x M18 B2 Battery pack, M12-18 C Charger, Tool bag
Article Number	4933448759
EAN Code	4002395810819

M18 GG | M18™ GREASE GUN

- Powerful 18V motor delivers over 690 bar max. operating pressure
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Extreme long run time - dispenses up to 7 cartridges per charge
- Strong handle balance and ergonomics - only 355 mm long and 3.9 kg
- Air bleeder valve - priming mechanism for quick flow
- Integrated hose storage, shoulder strap loop & LED fuel gauge - added user convenience and reducing down time
- Three way loading - bulk, cartridge and suction capable
- Grease capacity 400 ml cartridge, 473 ml bulk
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Supplied with 1219 mm high pressure flex hose with spring guard



	M18 GG-0
Pressure (bar)	690
Weight with battery pack (EPTA) (kg)	3.9 (M18 B2)
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied
Article Number	4933440493
EAN Code	4002395000357