

M12 CH

M12 FUEL

M12 FUEL™ SUB COMPACT SDS-PLUS HAMMER

- Industry's first brushless compact 12V rotary hammer with 1.1 Joules
- (EPTA), 0 6575 bpm & 0 900 rpm Exceptionally low vibration value 4.4 m/s² can be used for 8 hours in a
- Will drill over 60 50 mm x 6 mm holes per battery charge
 Superior power to weight ratio in its class with brushless POWERSTATE" motor for up to 3x longer motor life and up to 2x more run time
- PREDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool
- performance under load REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more
- 2-mode operation: choose rotary hammer or rotation only for maximum
- Optimised hammer drilling up to 6 10 mm (max 13 mm)
 43 mm neck size compatible with M12 DE dust extractor

M12 CH-0

Flexible battery system: works with all MILWAUKEE® M12™ batteries



PERFECT MATCH

SET OF 5 SDS-PLUS DRILL BITS, Ø 5 / 6 X 110 MM AND Ø 6 / 8 / 10 X 160 MM

Article Number



M12

M12



No batteries supplied, No 2 x M12 B6 Battery packs, charger supplied, No kitbox C12 C Charger, HD Box Kit included 4933451907 4002395282166

M12 H | M12™ SUB COMPACT SDS-PLUS HAMMER

M12 CH-602X

- Ergonomically designed, compact and light weight allows for work in
- tight spaces and reduces fatigue during all day use REDLINK™ overload protection electronics in tool and battery pack
- deliver best in class system durability L-shape, 2 mode hammer drill for hammer & rotary drilling for maximur
- versatility
- Low vibration at 6.7 m/s²
- Optimised hammer drilling up to 4 8 mm (max 13 mm)
 Individual battery cell monitoring optimises tool run time and ensures
- long term pack durability
- On board fuel gauge and LED light added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



| | M12 H-0 | M12 H-402C |
|---|---|---|
| Tool reception | SDS-Plus | SDS-Plus |
| Blow energy [EPTA][J] | 0.9 | 0.9 |
| No load speed (rpm) | 0 - 800 | 0 - 800 |
| Full load hammer action (bpm | 0 - 5350 | 0 - 5350 |
| Max. drilling wood (mm) | 10 | 10 |
| Max. drilling steel (mm) | 8 | 8 |
| Max. drilling concrete (mm) | 13 | 13 |
| Vibration drilling (m/s²) | 6.7 | 6.7 |
| Weight with battery pack (EPTA) (kg) | 1.8 (M12 B4) | 1.8 (M12 B4) |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 2 x M12 B4 Battery packs C12 C Charger, Kitbox |
| Article Number | 4933431355 | 4933443161 |
| EAN Code | 4002395243679 | 4002395003389 |

4932352338

M12 UDEL | M12™ UNIVERSAL DUST EXTRACTOR

- Eits all MII WALIKEE® SDS-plus and the majority of competitor's hammers between 41-61 mm neck size with just one adjustable side handle which can be mounted right or left of the hammer
- Delivering more than 40 min run time on a single M12 B2 2.0 Ah battery Due to telescopic nozzle capable of operating with up to 210 mm long SDS-plus drill bits
- Adjustable drilling depth gauge for a perfect adjustment to the task
 2 exchangeable nozzles with brushes to cover drilling diameters up to
- Ø30 mm (Ø5-16 mm, Ø16-30 mm)

 2 different vacuum modes to switch the unit either permanently on or
- activate it automatically when the actual drilling starts

 Automatic 5 sec switch off time delay to ensure a clean drill hole
- Equipped with a HEPA H13 class filter as well as a filter cleaning
- mechanism for best performance and a longer filter life time Equipped with a transparent tank for full capacity visibility as well as a Ø32 mm vacuum connector to empty the dust bin without any dust
- Fuel gauge displays remaining charge



| | M12 UDEL-0B | M12 UDEL-201B |
|--------------------------------------|------------------------|----------------------|
| Max. drill bit diameter [mm] | 30 | 30 |
| Max. drilling depth [mm] | 203 | 203 |
| Air volume (I/min) | 466 | 466 |
| Airflow speed [m per h] | 28 | 28 |
| Capacity liquids (I) | 0.31 | 0.31 |
| Capacity solids (I) | 0.31 | 0.31 |
| Filter type | HEPA H13 | HEPA H13 |
| Max. vacuum (mbar) | 23.4 | 23.4 |
| Weight with battery pack (EPTA) (kg) | 2.2 (M12 B2) | 2.2 (M12 B2) |
| | No batteries supplied, | 1 x M12 B2 Battery |
| Kit included | No charger supplied, | pack, C12 C Charger, |
| | Tool bag | Tool bag |
| Article Number | 4933471460 | 4933471462 |
| EAN Code | 4058546290887 | 4058546299132 |

For further technical specifications, including noise and vibration data, please visit our website: www.milwaukeetool.co.uk

M12 FPD2 | M12 FUEL" SUB COMPACT PERCUSSION DRILL

- Extremely compact design of 152 mm length for access into tight
- *45 Nm of torque superior power to size ratio
 *13 mm heavy duty metal chuck for quick bit changes and bit retentior
 *Mechanical clutch with 13 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer
- on hoard fuel gauge, metal belt clip and LED light

 on board fuel gauge, metal belt clip and LED light

 technologies. MILWAUKEE®s POWERSTATE™ brushless motor,

 REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence
- delivering outstanding power, run time and durability
 Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

| | M12 FPD2-602X |
|--------------------------------------|--|
| No load speed gear 1 (rpm) | 0 - 450 |
| No load speed gear 2 (rpm) | 0 - 1,550 |
| Chuck capacity (mm) | 13 |
| Max. drilling wood (mm) | 35 |
| Max. drilling steel (mm) | 13 |
| Max. drilling masonry (mm) | 13 |
| Max. percussion rate (bpm) | 0 - 22,500 |
| Max. torque (Nm) | 45 |
| Weight with battery pack (EPTA) (kg) | 1.4 (M12 B6) |
| Kit included | 2 x M12 B6 Battery packs, C12 C Charger, |
| | HD Box |
| Article number | 4933479871 |
| EAN code | 4058546376659 |
| | |

M12 FDD2 M12 FUEL" SUB COMPACT DRILL DRIVER

- Extremely compact design of 151 mm length for access into tight
- 45 Nm of torque superior power to size ratio
- 13 mm heavy duty metal chuck for quick bit changes and bit retentio
 Mechanical clutch with 13 torque settings, plus 1 for locked clutch
- on board fuel gauge, metal belt clip and LED light

 The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor,
- REDLITHIUM" battery pack and REDLINK PLUS" electronic intelliger delivering outstanding power, run time and durability

 Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

M12 FDD2-602X No load speed gear 1 (rpm) No load speed gear 2 (rpm) Chuck capacity (mm) Max. drilling steel (mm) Max. torque (Nm) Weight with battery pack (EPTA) (kg) 1.4 (M12 B6) 2 x M12 B6 Battery packs, C12 C Charger HD Box 4933479970

M12 FDDX | M12 FUEL™ INSTALLATION DRILL/DRIVER WITH INTERCHANGEABLE HEADS

- High performance compact 4-in-1 installation drill for extreme versatility
- Removable chuck system with 4 different heads for multiples of
- ¼" hex drive behind chuck fitting, reduces drill length to 130 mm when In-line grip for unrivaled access and control
- Brushless POWERSTATE™ motor delivers up to 34 Nm of torque
- Magnetic holder for easy bit access
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence
- delivering outstanding power, run time and durability Flexible battery system: works with all MILWAUKEE® M12™ batteries



| ANGEABLE HEADS | | |
|--------------------------------------|---|--|
| | M12 FDDXKIT-202X | |
| No load speed gear 1 (rpm) | 0 - 400 | |
| No load speed gear 2 (rpm) | 0 - 1600 | |
| Chuck capacity (mm) | 10 | |
| Max. drilling wood (mm) | 28 | |
| Max. drilling steel (mm) | 10 | |
| Max. torque (Nm) | 34 | |
| Weight with battery pack (EPTA) (kg) | 0.90 (M12 B2) | |
| Standard equipment | 10 mm metal chuck, right angle attach- ment, offset attachment and 6mm hex attachment | |
| Kit included | 2 x M12 B2 Battery packs, C12 C Charger HD Box | |
| Article Number | 4933464980 | |
| EAN Code | 4058546229252 | |

M12 FPDX | M12 FUEL™ SUB COMPACT PERCUSSION DRILL WITH REMOVABLE CHUCK



- High performance compact 6-in-1 percussion drill system for extreme versatility
- · Removable chuck system with 3 different heads for multiples of
- applications Brushless POWERSTATE™ motor delivers up to 44 Nm of torque
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- 13 mm keyless chuck, full metal right angle 1/4" hex drive head and full metal offset 1/4" hex drive head
- 1/4" hex drive behind chuck fitting, reduces drill length to 138 mm when required
- Full metal planetary gearbox transmission for extreme durability
- LED light for workspace illumination
 Flexible battery system: works with all MILWAUKEE® M12™ batteries



| | M12 FPDXKIT-602X |
|--------------------------------------|---|
| No load speed gear 1 (rpm) | 0 - 450 |
| No load speed gear 2 (rpm) | 0 - 1700 |
| Chuck capacity (mm) | 13 |
| Max. drilling wood (mm) | 35 |
| Max. drilling steel (mm) | 13 |
| Max. drilling masonry (mm) | 13 |
| Max. percussion rate (bpm) | 0 - 25,500 |
| Max. torque (Nm) | 37 |
| Weight with battery pack (EPTA) (kg) | 1.5 (M12 B6) |
| | Removable chuck, offset attachment, right |
| Standard equipment | angle attachment |
| I/A to alcode at | 2 x M12 B6 Battery packs, C12 C Charger |
| Kit included | HD Box |
| Article Number | 4933464189 |
| EAN Code | 4058546221348 |