


## Plugs and connectors – Connectors

to DIN VDE 0623, EN 60309-2. Other voltages and frequencies available on request. Products with pilot contact available on request.




**Connector AM-TOP**  
single part body

\* For use on camping sites, please select type 180AC

IP 44  
Std. Pack. Qty: 10

A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	3	509	510*	511		2441	2517
16	4	512	513	514	515	516	517
16	5	518	519	5	2026	2193	2495
32	3	521	522	523		2196	2674
32	4	524	525	526	527	528	529
32	5	530	531	6	2027	2245	2493




**Connector ProTOP**  
cable gland and sealing

\* For use on camping sites, please select type 180AC

IP 44  
Std. Pack. Qty: 10

A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	3	179A	180A*	181A			
16	4		193A	194A	195A		
16	5			15A			
32	3	121	122				
32	4		125	126	127		
32	5			16A			




**Connector StarTOP**  
screwless, with insulation displacing technique, SafeCONTACT, cable gland and sealing

\* For use on camping sites, please select type 180AC

IP 44  
Std. Pack. Qty: 10

A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	3	979	980*				
16	4		993	994	965	996	
16	5			35			
32	3	725	731				
32	4		761	763	765		
32	5			36			



**Connector PowerTOP Xtra**  
X-CONTACT, rubberised grip area, frame terminals, cable gland and sealing

IP 44  
Std. Pack. Qty: 5

A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
63	3	14101	14102				
63	4		14105	14106	14107		
63	5		14111	14112			

NEW

X-CONTACT

INSIDE



**Get more information on the new generation of contact sleeves:**  
on page 26 or at [www.x-contact.info](http://www.x-contact.info)

