


# Mercurial




- Utility LED wall/ceiling luminaire suitable for education and commercial applications and ancillary areas
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire (AMER1/1/\*\* only)
- Corridor function options available for effective reduction in energy consumption
- Side conduit entry covers retain sleek appearance when not in use
- Clip in gear tray ensures quick installation



**OCTO**  
Option Available

Powered by  
**CASAMBI**



Silver

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
220/240V	50/60Hz	-20°C to 40°C	L70 80,000	80	3	120°	2	IP54	IK07

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	A
AMER1/1/W	CCT Selectable - White 370mm	13/20W	3000K/4000K	1900lm - 2700lm(4000K)	135lm/w (4000K)	370mm
AMER1/1/S	CCT Selectable - Silver 370mm					
AMER2/1/W	CCT Selectable - White 500mm	34W	3000K/4000K	4700lm (4000K)	130lm/w (4000K)	500mm
AMER2/1/S	CCT Selectable - Silver 500mm					

CODE (OPTIONS)	DESCRIPTION
/SM3	Self-Test Emergency
/DM3	DALI emergency
/OCTO	OCTO Smart Control

CODE (OPTIONS)	DESCRIPTION
/MWS	Integral Microwave Sensor
/DD	Digital Dimming (DD1/DD3/DD4)
/CF	Corridor Function

CODE (ACCESSORIES)	DESCRIPTION
ABSK/3	Bulkhead Suspension Kit

