

LR, Gewinding; schwarz (RAL 9005) oder weiß (RAL 9010)

LR, lock ring; black (RAL 9005) or white (RAL 9010)



Material				Temp.	
PVC-U				-5°C/+60°C	
art	dn	ps	pl	ref	
				schwarz black	weiß white
LR 20	20,0	250	10000	009 542	009 594
LR 25	25,0	200	8000	009 543	009 595

LN, Gewindemutter; schwarz (RAL 9005) oder weiß (RAL 9010)


LN, lock nut; black (RAL 9005) or white (RAL 9010)



Material				Temp.	
PVC-U				-5°C/+60°C	
art	dn	ps	pl	ref	
				schwarz black	weiß white
LN 16	16,0	200	8000	009 535	009 587
LN 20	20,0	200	8000	009 536	009 588
LN 25	25,0	100	4000	009 537	009 589
LN 32	32,0	100	2400	009 538	009 590
LN 40	40,0	30	1200	009 539	009 591
LN 50	50,0	25	1000	009 540	009 592

Biegefeder, für starre Rohre; zur Herstellung individuell angepasster Bögen

Bending spring, for rigid conduits; for customised conduit bends



art	dn	ps	ref
für Rohrtypen UPRM, BSSH for conduit types UPRM, BSSH			
BS 16	16	1	020 795
BS 20	20	1	020 796
BS 25	25	1	020 797
für Rohrtype VRM for conduit type VRM			
BSL 20	20	1	009 135
BSL 25	25	1	009 136
für Rohrtypen HFIR, HFIRM for conduit types HFIR, HFIRM			
BS 16 SE	16	1	084 064
BS 20 SE	20	1	084 065
BS 25 SE	25	1	084 066
für Rohrtype HFPRM for conduit type HFPRM			
BS 16	16	1	020 795
PBF 11	20	1	000 931
PBF 16	25	1	000 933