


DATASHEET



BT14ACTS

230V IP65 14W CCT Adjustable LED Bulkhead with Sensor

www.mlaccessories.co.uk



| MLA PART CODE | BT14ACTS |
|-------------------------------|---|
| DESCRIPTION | 230V IP65 14W CCT Adjustable LED Bulkhead with Sensor |
| NET WEIGHT (KG) | 0.88 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Diameter - 315 Projection - 74 |
| CONSTRUCTION | Construction - Polycarbonate |
| CLASS | II |
| IP RATING | IP65 |
| IK RATING | IK08 |
| WATTAGE (W) | 14 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 1130 / 1260 / 1210 |
| LUMENS LIGHT SOURCE ONLY (LM) | 1340 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 109.9 |
| CIRCUIT WATTAGE (W) | 12.19 |
| CCT | 3000/4000/5700K |
| LIGHT COLOUR | CCT |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.058 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.567 |
| PST-LM | 0.027 |
| BEAM ANGLE (DEGREES) | 115 |
| LIFE SPAN (HRS) | 30,000 |

| | |
|--|---|
| L70B50 LIFESPAN (HRS) | 50,000 |
| LED COMPATIBLE | Yes |
| DIMMABLE | No |
| OPERATING TEMPERATURE | -20~50°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE ENTRY (MM) | 20 |
| CABLE GLAND INCLUDED | Blind grommet |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 14W OUTPUT VOLTAGE - 30 - 43V OUTPUT CURRENT - 320mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 83 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C |
| SENSOR TYPE | Microwave |
| SENSOR OVERRIDE | No |
| SENSOR DETECTION ANGLE (DEGREES) | 150 |
| OPTIMUM DETECTION RANGE (M) | 1m ~ 6m ceiling mounted @ 3m; 2m ~ 18m wall mounted @ 2m; mounting height 6m max. |
| SENSOR DURATION | 5 seconds - 30 minutes |
| SENSOR LUX SETTINGS | 2 lux - 50 lux / Disable |
| STANDBY POWER | <0.5W |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270825435 |

Date Created: 21/04/2022 09:03

