

Product Code: CMA052

Description: 13A Double Pole Switched Fused Connection Unit With Neon & Optional Flex Outlet



General Information

Dimensions	86mm (W) x 86mm (H) x 9.5mm (D)
Material Composition	Front Plate, Rocker Switch & Fuse Drawer: Urea Rear Housing: Urea Neon Lens: Polycarbonate Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz
Fixing Centres	60.3mm
Terminal Size	5mmø
Terminal Torque	2.5Nm
Terminal Capacity	4 x 2.5mm ² or 2 x 4mm ²
Switched	Yes
Double Pole	Yes
Twin Earth Terminals	Yes
Neon Indicator	Yes
Flex Outlet	Yes
Back Box Depth	25mm Minimum
Temperature Rating	-5°C to +40°C
Warranty	20 Years

Standards BS 1363-4: 2016 +A1: 2018

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.
All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.