

Nitro

Standard non-maintained emergency downlight

Battery warranty

5
YEAR

Temp. Control




- Standard and corridor version with different lens
 - Non-maintained, 3hrs
 - Available in white or black

50mm
Cut-out

▲ Standard White



▲ Corridor White



▲ Standard Black



Standard Lens

Order Code	Finish	Input Power (max)	Emergency Output Power	Beam Angle	CCT	Lumen
NTR03	White	2.5W	1.5W	45°	6000K	150lm
NTR03-BLK	Black					130lm

Corridor Lens

Order Code	Finish	Input Power (max)	Emergency Output Power	Beam Angle	CCT	Lumen
NTR03/COR	White	2.5W	1.5W	25°(Transverse) 120°(Axial)	6000K	200lm

Battery

Order Code	Type	Capacity	Voltage
BATC18LFP1	LiFePO4	1800mAh	3.2V

5 5 Years
Product Warranty2 2 Years
On-Site Warranty1000V
Surge ProtectionPush-wire terminal block
includedGeneral
Specification

Input Voltage	220-240Vac 50/60Hz
Input Current (max)	20mA
Lifetime	50,000h
Emergency Conversion Time	< 1s
Emergency Operation Time	3h
Charging Time	24h
Ambient Temp	0°C to 50°C
Maximum Case Temp	75°C
Housing	Polycarbonate



Order Code

NTR03
NTR03-BLK
NTR03/COR

Dimensions

