



Wide range of switches, energy sockets (compliant with national and international standards), data sockets, devices for the management of climate control, comfort, technical alarms signalling, emergency lighting. The Chorus modular devices are available in four colors, glossy white, satin black, painted titanium and glossy ivory and in different modularities, 1/2, 1, 2 and 3 modules. Thanks to the frame supports for rectangular, square and round boxes, the devices allow you to create endless combinations with the range of Chorus plates.

Category	USB power supply	Colour	Black
Output voltage	5V dc	Max current supplied	2,1 A
Standard	EN 60950-1; EN 61000-6-1; EN 61000-6-3	Wiring terminals	With screw
Terminal tightening capacity stranded cables (mm2)	min. 1 - max. 2x1,5	Terminal tightening capacity solid cables (mm2)	min. 1 - max. 2x1,5
No. Chorus modules	1	Electrocod	0144

DIMENSIONAL

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 14/05/2019

Data, measures, designs and pictures are shown only as informativ purposes, and could be changed without previous notice