

GW20510



### PUSH-BUTTONS - 250V AC

Code	Description	Type	Symbol	No. SYSTEM modules	Pack Carton
GW 20 510	1P NO - 10A	General		1	80/160
GW 20 511	1P NO - 10A	With symbol	Key	1	15/30
GW 20 512	1P NO - 10A	With symbol	Bell	1	15/30
GW 20 513	1P NO - 10A	With symbol	Light	1	15/30
GW 20 514	1P NO - 10A	With symbol	Stairs	1	15/30
GW 20 515	1P NO - 10A	Backlit 230V ac (0.4W)		1	30/60
GW 20 516	1P NO - 10A	Backlit 12/24V (0.8W)		1	30/60
GW 20 529	1P NO - 10A	Illuminable		1	30/60
GW 20 531	1P NC - 10A	Illuminable		1	15/30
GW 20 519	1P NC - 10A	General	Circle	1	15/30
GW 20 520	1P NO+NO - 10A	With interlock	Double circles	1	15/30
GW 20 521	1P NO+NO - 10A	With interlock	UP - DOWN	1	30/60
GW 20 522	1P NO - 10A - Aux. NC	Start	Green	1	30/60
GW 20 523	1P NC - 10A - Aux. NO	Stop	Red	1	30/60
GW 20 517	2P NO - 10A	General	Double circle	1	30/60
GW 20 518	2P NO - 10A	With pull-cord		1	20/40
GW 20 530	2P NO - 10A	With key	0/1	1	15/30

**CHARACTERISTICS:** GW20529, supplied without lamp. It uses miniature lamps. GW20520, GW20521, both contacts are open in the central (OFF) position.  
**ACCESSORIES SUPPLIED:** GW20515 red miniature lamp, GW 20516 white miniature lamp. GW20518, cord in insulating material, 140cm long with knob.

GW20024



### PUSH-BUTTONS WITH BACKLIT NAME-PLATE - 250V AC

Code	Description	Type	Lamp	Lamp voltage	Lamp power	No. SYSTEM modules	Pack Carton
GW 20 591	1P NO - 10A	Illuminable	Cartridge lamp S6x36 mm	12 - 24V	2 W	2	15/30
GW 20 024	1P NO - 10A	Illuminable	Cartridge lamp S6x36 mm	12 - 24V	2 W	3	20/40

**CHARACTERISTICS:** Supplied without lamp.

GW20589



### WIDE-BUTTON ILLUMINABLE CONTROL DEVICES - 250V AC

Code	Description	Type	No. SYSTEM modules	Pack Carton
GW 20 589	1P - 16AX	Two-way switch	2	15/30
GW 20 580	1P - 16AX	Intermediate switch	2	1/15
GW 20 527	1P NO - 10A	Push-button	2	15/30

**CHARACTERISTICS:** Supplied without lamp.

## BLANKING MODULES AND OUTLET

GW20056



### BLANKING MODULES AND CABLE OUTLET

Code	Description	No. SYSTEM modules	Pack Carton
GW 20 056	1 gang	1	10/480
GW 20 073	2 gang	2	30/60
GW 20 058	1 gang with outlet for cable Ø 4 and Ø 8mm	1	60/120

**APPLICATIONS:** in addition to their normal use, they permit installing signal socket-outlets, microswitches and LEDs after appropriate drilling/preparation.  
 In addition, it is possible to apply the temperature sensor GW30703 using the special double-sided adhesive.