

PROTECTION - SYSTEM WHITE

MINIATURE CIRCUIT BREAKERS

GW20431



MINIATURE CIRCUIT BREAKERS - CHARACTERISTIC C - 230V AC

Code	Description	Rated current (A)	No. SYSTEM modules	Pack Carton
BREAKING CAPACITY: 3 kA				
GW 20 431	Single pole (1P)	6	1	15/30
GW 20 432	Single pole (1P)	10	1	15/30
GW 20 433	Single pole (1P)	16	1	15/30
GW 20 434	Two-pole (1P+N)	6	1	15/30
GW 20 435	Two-pole (1P+N)	10	1	15/30
GW 20 436	Two-pole (1P+N)	16	1	15/30

SYSTEM RANGE

GW20437



RESIDUAL CURRENT MINIATURE CIRCUIT BREAKERS - CHARACTERISTIC C - CLASS A - 230V AC

Code	Description	Idn	Rated current (A)	No. SYSTEM modules	Pack Carton
BREAKING CAPACITY: 3 kA					
GW 20 437	Two-pole (1P+N)	10 mA	6	2	1/15
GW 20 438	Two-pole (1P+N)	10 mA	10	2	1/15
GW 20 439	Two-pole (1P+N)	10 mA	16	2	1/15
GW 20 448	Two-pole (1P+N)	30 mA	6	2	1/15
GW 20 449	Two-pole (1P+N)	30 mA	10	2	1/15
GW 20 450	Two-pole (1P+N)	30 mA	16	2	1/15

GW20454



RED MINIATURE CIRCUIT BREAKERS FOR DEDICATED CIRCUITS - CHARACTERISTIC C - 230V AC

Code	Description	Rated current (A)	No. SYSTEM modules	Pack Carton
BREAKING CAPACITY: 3 kA				
GW 20 454	Two-pole (1P+N)	6	1	15/30
GW 20 455	Two-pole (1P+N)	10	1	15/30
GW 20 456	Two-pole (1P+N)	16	1	15/30

PROTECTION DEVICES

GW20401



FUSE-HOLDER - 250V AC

Code	Rated current (A)	Fuse type	No. SYSTEM modules	Pack Carton
GW 20 401	16	Ø 6.3 x 32 mm	1	30/60

GW20423



SURGE PROTECTION DEVICE - 250V AC

Code	Max. dischargeable energy	Maximum discharge current	No. SYSTEM modules	Pack Carton
GW 20 423	75 J	8 kA (8/20 µs)	1	1/14

APPLICATIONS: protection of electronic equipment (TV - HI-FI - computers, etc.) from overvoltage of atmospheric or manoeuvring origin that may be conveyed by the supply lines.