

- 5 Years**
Product Warranty
- 2000V**
Surge Protection
(L to GND)
- Mains Dimmable**
Dimmable




Recommended



Emergency Kit
Neka P112



Mauna PIR sensor
P30



Uni-Remote
RMT-UNI

General Specification

Voltage 220-240Vac
50/60Hz
CRI >80
SDCM <6
L70B50 Lifetime 147000h
Power Factor 0.88(6W)
0.86(4.5W)
Ambient Temp -30°C to 50°C
Housing Zinc coated
sheet steel+PC





Mauna III Plus Fixed

6W / 4.5W Dimmable Fire-rated Downlight with Bezel Finish Options

- Switchable wattage and CCT (2700/3000/4000/6000K)
- Optional add-on emergency kits, available in standard and self-test
- Optional PIR sensors compatible with Uni-Remote
- Integrated dimmable driver
- Interchangeable magnetic bezels with different finishes
- Can be installed under Insulation layer
- Compact size with a void of only 43mm
- Acoustically rated in accordance with BS EN ISO 10140-2:2021 and BS EN ISO 10140-3:2021
- Coloured LENSEL push-wire terminals

- E+** Add-on emergency
- S+** Plug-in ON/OFF sensor
- S+** Plug-in corridor sensor
- Watt** Wattage switching
- CCT** CCT switching
- M** Magnetic bezel
- ECO** Modular design
- Uni-Remote Compatible**



Push-wire lever
terminals included

Interchangeable bezels



Energy Class: **F** **A** **G**

Order Code	Default Power	Alternative Power	Beam Angle	CCT	Lumen*
MAU306PL	-	4.5W	60°	Switchable**	500lm (380lm) (2700K)
					510lm (395lm) (3000K)
					530lm (410lm) (4000K)
					530lm (410lm) (6000K)
	6W	-	60°	Switchable**	650lm (470lm) (2700K)
					670lm (500lm) (3000K)
					710lm (520lm) (4000K)
					710lm (520lm) (6000K)

* Total lumen (lumen measured in 90° Cone)

** When CCT switchable, colour temperature switches between 2700, 3000K, 4000K & 6000K

Interchangeable bezels

Order Code	MAUBZ-BAS	MAUBZ-BLK	MAUBZ-WHT	MAUBZ-CHM	MAUBZ-SCH	MAUBZ-ABR
Order Code	MAUBZ-BBR	MAUBZ-BNI	MAUBZ-AGR			
Order Code	MAUBZ-SBAS	MAUBZ-SBLK	MAUBZ-SWHT	MAUBZ-SCHM	MAUBZ-SSCH	MAUBZ-SABR

Optional Gears

Type	Order Code	Description
Emergency kit	EMPAD01	Standard emergency kit
Emergency kit	EMPAD01/SST	Standard & Self-test 2 in 1 emergency kit
PIR sensor	MAUPIR	ON/OFF Fire-Rated PIR sensor
PIR sensor	MAUPIR/D	ON/OFF/ Phase-cut Dimming Fire-Rated PIR sensor

Accessory

Type	Order Code	Description
Remote Control	RMT-UNI	Universal Remote Control for PIR sensors

RF wireless triac dimmer

Order Code	Max Power	Output Current
CYDIMRFT1	2 x 120W (100 Vac) 2 x 288W (240 Vac)	2 x 1.2 A

* See datasheet for recommended number of lamps per dimmer

Order Code

MAU306PL

MAUBZ-BAS
MAUBZ-BLK
MAUBZ-WHT
MAUBZ-CHM
MAUBZ-SCH
MAUBZ-ABR
MAUBZ-BBR
MAUBZ-BNI
MAUBZ-AGR

MAUBZ-SBAS
MAUBZ-SBLK
MAUBZ-SWHT
MAUBZ-SCHM
MAUBZ-SSCH
MAUBZ-SABR

Dimensions

