





CMA034



CMA038



CMA039



CMA935  
Non-standard socket



CMA936  
Non-standard socket



CMA675



PA380WH  
Non-standard plug



CMA736



CMA735



CMA771U



CMA770



CMA780

**Round Pin Socket Outlets**

- CMA034 15A Switched Round Pin Socket
- CMA038 5A Round Pin Socket
- CMA039 2A Round Pin Socket

**Lockable Socket**

- CMA675 13A 1G DP Key Lockable Socket With Neon

**Non-Standard Socket Outlets**

- CMA935 13A 1 Gang DP Switched Non-Standard Socket
- CMA936 13A 2 Gang DP Switched Non-Standard Socket

**Non-Standard Resilient Plug Tops**

- PA380WH 13A Fused Non-Standard Plug - White
- PA380RD 13A Fused Non-Standard Plug - Red

For use with non-standard Click® Mode sockets CMA935 and CMA936

**Locating Plug Sockets**

- CMA735 13A 1 Gang DP Switched Locating Plug Socket
- CMA736 13A 2 Gang DP Switched Locating Plug Socket With Outboard Rockers

**Switched Sockets With USB Outlets**

- CMA771U 13A 1 Gang Switched Socket With 2.1A USB Outlet (Twin Earth)
- CMA770 13A 2 Gang Switched Socket With 2.1A USB Outlet (Twin Earth)
- CMA780 13A 2 Gang Switched Socket With Twin 2.1A USB Outlets (4.2A) (Twin Earth)

Standards: BS 546, BS 1363 675: BS 1363-2, BS EN 60669-1  
 Back Box Depth: 25mm Minimum 675: 35mm Minimum  
 Cable Size: 2A: 2 x 2.5mm<sup>2</sup> / 3 x 1.5mm<sup>2</sup> 13A: 4 x 2.5mm<sup>2</sup> / 2 x 4mm<sup>2</sup> 675: 3 x 2.5mm<sup>2</sup>, 2 x 4mm<sup>2</sup>  
 Dimensions: 1 Gang: (86mm x 86mm x 9.5mm), 2 Gang: (146mm x 86mm x 9.5mm)

Standards: 735, 736: BS 1363, 770, 780, 771U: BS1363-2: 2016 +A1: 2018, BS EN 62368-1 BS EN 62680-1-1  
 Back Box Depth: 25mm Minimum Cable Size: 4 x 2.5mm<sup>2</sup> / 2 x 4mm<sup>2</sup>  
 Dimensions: 1 Gang: (86mm x 86mm x 9.5mm), 2 Gang: (146mm x 86mm x 9.5mm)