

3 3 Years
Product Warranty

2000V
Surge Protection
(L to GND)



Optional Connector
KCWP3IN

General Specification





Voltage 220-240Vac
50/60Hz
CRI 80
SDCM 6
L80B10 Lifetime 83000h
Power Factor 0.90
Ambient Temp -20°C to 50°C
Housing Die-cast aluminium



Order Code

RHI310-SCT
RHI320-SCT
RHI330-SCT
RHI350-SCT

Dimensions



Rhine III

Upgrade
Jul. 2025

LED flood light

- Switchable CCT (3000/4000/6500K)
- Die-cast aluminium body
- Surge protection
- Slim profile
- 1m of H05RN-F 3 x 1mm² cable



CCT switching



Wildlife friendly*

*CCT of 3000K



Angled bracket for easy installation

Energy Class: **E**

Order Code	Power	Beam Angle	Finish	CCT	Lumen
RHI310	10W	110°	Black	Switchable*	1100lm (3000K)
					1150lm (4000K)
					1100lm (6500K)
RHI320	20W	110°	Black	Switchable*	2200lm (3000K)
					2300lm (4000K)
					2200lm (6500K)
RHI330	30W	110°	Black	Switchable*	3300lm (3000K)
					3450lm (4000K)
					3300lm (6500K)
RHI350	50W	110°	Black	Switchable*	5500lm (3000K)
					5750lm (4000K)
					5500lm (6500K)

* When CCT switchable, colour temperature switches between 3000K, 4000K & 6500K

Accessory

Type	Order Code	Description
Connector	KCWP3IN	IP67 In-line Connector