

Upgrade
Jul. 2025

Rhine III Sensor

LED flood light with PIR sensor

Built-in motion sensor



CCT switching



Wildlife friendly*



*CCT of 3000K


Uni-Remote Compatible



- Switchable CCT (3000/4000/6500K)
 - Die-cast aluminium body
 - Adjustable PIR sensor
- Configurable with the Uni-Remote
 - Surge protection
 - Slim profile
- 1m of H05RN-F 3 x 1mm² cable



1m lead



Angled bracket for easy installation



OFF/ON twice within 3 seconds to override the PIR sensor

Energy Class: **E**

Order Code	Power	Beam Angle	Finish	CCT	Lumen
RHI310/S	10W	110°	Black	Switchable*	1100lm (3000K) 1150lm (4000K) 1100lm (6500K)
RHI320/S	20W	110°	Black	Switchable*	2200lm (3000K) 2300lm (4000K) 2200lm (6500K)
RHI330/S	30W	110°	Black	Switchable*	3300lm (3000K) 3450lm (4000K) 3300lm (6500K)
RHI350/S	50W	110°	Black	Switchable*	5500lm (3000K) 5750lm (4000K) 5500lm (6500K)

* When CCT switchable, colour temperature switches between 3000K, 4000K & 6500K

Accessories


Type	Order Code	Description
Remote Control	RMT-UNI	Universal Remote Control
Connector	KCWP3IN	IP67 In-line Connector

3 3 Years
Product Warranty

2000V
Surge Protection
(L to GND)



Optional Connector
KCWP3IN



Uni-Remote
RMT-UNI
(Required)

General Specification


Voltage 220-240Vac
50/60Hz
CRI 80
SDCM 6
L80B10 Lifetime 83000h
Power Factor 0.90
Ambient Temp -20°C to 50°C
Housing Die-cast aluminium




Order Code

RHI310-SCT/S
RHI320-SCT/S
RHI330-SCT/S
RHI350-SCT/S


Dimensions




RHI310/S



RHI320/S



RHI330/S



RHI350/S