



WMPS11

Wall Switches

Characteristics:

- Unique patented loop terminal allows neutral looping at the switch.
- Complies with BS EN 60669-1, a.c only.
- 'X' rated - No need to derate for fluorescent loads.
- Clear terminal markings: 1-way L1, 2-way L2
- Capacity of each terminal - 2 x 4.0mm² conductors.
- For mounting boxes see selection chart on page 56.
- For multigang switches use of a 25mm mounting box will provide increased wiring space.
- Supplied with M3.5 x 20mm long fixing screws and screw covers.

Description

Cat ref.

10AX Wall Switches

| | |
|----------------------------|-------------------|
| 1 Gang 1 Way | WMPS11 |
| 1 Gang 1 Way Printed 'Fan' | WMPS11/FAN |
| 1 Gang 2 Way | WMPS12 |
| 2 Gang 2 Way | WMPS22 |
| 3 Gang 2 Way | WMPS32 |
| 4 Gang 2 Way | WMPS42 |
| 6 Gang 2 Way | WMPS62 |
| 1 Gang 2 Way Wide Rocker | WMPS12W |
| 2 Gang 2 Way Wide Rocker | WMPS22W |



WMPS16

Intermediate Switches

Characteristics:

- Complies with BS EN 60669-1, a.c only.
- 'X' rated - No need to derate for fluorescent loads.
- Clear terminal markings.
- Capacity of each terminal - 2 x 4.0mm² conductors.
- For mounting boxes see selection chart on page 56.
- For multigang switches use of a 25mm mounting box will provide increased wiring space.
- Supplied with M3.5 x 20mm long fixing screws and screw covers.

Description

Cat ref.

Intermediate Switch

WMPS16



WMPS12W

Push Switches

Characteristics:

- Unique patented loop terminal allows neutral looping at the switch.
- Complies with BS EN 60669-1, a.c only.
- 'X' rated - No need to derate for fluorescent loads.
- Clear terminal markings: 1-way L1, 2-way L2
- Capacity of each terminal - 2 x 4.0mm² conductors.
- For mounting boxes see selection chart on page 56.
- For multigang switches use of a 25mm mounting box will provide increased wiring space.
- Supplied with M3.5 x 20mm long fixing screws and screw covers.

Description

Cat ref.

Push Switches

| | |
|-------------------|-----------------|
| Retractive Switch | WMPS12R |
| With Bell Symbol | WMPS12RB |
| With Wide Rocker | WMPS12RW |



WMPS3PIF

Isolator Switches

Characteristics:

- Complies with BS EN 60669-2-4
- Rated conditional short circuit current (I_{nc}) 1500A tested with Hager **MTN110** 6kA B curve MCB.
- Capacity of each terminal 2 x 4.0mm² conductors.
- For mounting boxes see selection chart on page 56.
- Supplied with M3.5 x 20mm long fixing screws and screw covers.

Description

Cat ref.

3 Pole Isolator Switches

| | |
|---------------------------------|-----------------|
| Isolator Switch | WMPS3PI |
| Isolator Switch with Fan Symbol | WMPS3PIF |